

## Granite step cement foundation specification sheet

The following specifications must be met before we, Landscapers Depot can perform any installation of granite steps at your home or business. Please read and check off the items bellow and sign that you understand what is needed to be done.

- Surface must be screeded and troweled smooth and flat all the way to the foundation.
- All four corners must be level with a 1/4" pitch away from the house for proper water drainage.
- No bumps or irregularities in the pad.
- Pad must be no shorter then the width of the steps being installed (i.e. 6' wide steps, pad can not be shorter then 72").
- Pad must be no shorter then 3" of the total depth of the step set (please see below to calculate this measurement).
- Pad height from door sill must be divisible by 7". Please give 1/2" space for total height.
- Rebar reinforcement. *(Optional)*
- All Siding or wood paneling material must be removed and out of the way 6" from the width of the cement pad *(Landscapers depot installation crews are not allowed nor are they licensed to do any physical work to the house itself)*
- Existing cement pads are not acceptable unless they meet the requirements above.
- Work area must not have any fences, trees, rocks, etc that is narrower then 110" for the forklift to pass thru. If a crane truck is used in the installation please be aware of any power lines or tree limbs that may cause an obstruction. Crane truck must get within 20' of the installation.

### DEPTH AND WIDTH OF YOUR PAD

The width of your pad is the length of the steps that you ordered. The width of your pad is the total depth of your landing plus steps, use the formula below to calculate your depth of the cement pad.

Depth of landing \_\_\_\_ + number of steps \_\_\_\_ = total depth of pad \_\_\_\_

Width and depth of pad \_\_\_\_ x \_\_\_\_

If your pad was professionally installed please fill out his contact info below

Company \_\_\_\_\_ Contact name \_\_\_\_\_

Phone number \_\_\_\_\_ Date completed \_\_\_\_\_

.....

Your signature below states that you have read the above requirements and have met them. If a installation crew arrives at your house or business and cannot complete the installation because the above requirements were not completed a fee of \$85 dollars per hour starting from the time left from the yard will be charged. If the installation can not be completed for any reason the delivery will have to be rescheduled.

X \_\_\_\_\_ Date \_\_\_\_\_

I request a crane truck or otherwise all installations will be done by fork truck

Crane truck installation is \$100.00 per hour from the time that the truck leaves the yard to the time it arrives back at the yard after installation.